



CITC Technical Specification

Document Number: RI114
Revision: Issue 1
Date: 17/02/2019 G

Specification for License - exempt LPWAN Devices and Ancillary Equipment

Issued by The Communications and Information Technology Commission of Saudi Arabia in accordance with article 89 of the Telecommunications Bylaw.

Communications and Information Technology Commission
Alnakheel Quarter
Riyadh

Telephone: + 966 11 461 8000
Fax: + 966 11 461 8120
E-mail: info@citc.gov.sa
Website: www.citc.gov.sa

Contents

This document comprises the following sections:

Scope.....	2
Responsibility for deployment and non-protected status.....	2
Entry into force	3
Frequency of operation	3
Proof of compliance	4
Technical requirements	4
Additional requirements	5
Obtaining technical standards	5
Network information (only for network interfaces)	5
Document history.....	5

Scope

This document generally applies to any type of License - exempt LPWAN devices and ancillary equipment. In particular, this specification describes the requirements applicable to Low Power-Wide Area Network applications deployed in unlicensed SRD bands, including all kinds of terminal nodes and network access points/base stations.

All telecommunications and radio terminal equipment must comply with the relevant technical specifications established by CITC. In addition, such equipment may be subject to regulations for Declaration of Conformity or registration. See <http://www.citc.gov.sa/> for details.

If more than one interface type is offered by a piece of equipment, each interface must meet the applicable technical specifications.

Responsibility for deployment and non-protected status

Deployment of License - exempt LPWAN devices, must be carried out by qualified personnel. Using such networks for provision of services to third parties is subject to licensing from CITC.

In any case, end users must be informed by service providers prior to deploying and activating such License - exempt LPWAN devices that their utilisation of unlicensed frequency bands carries the risk of interference from other users of shared bands, with possible detrimental effect on quality of service, such as data throughput degradation, packet loss, packet transmission delay, etc.

CITC will not assume responsibility for investigating/resolving any cases of interference/service degradation between the users of shared unlicensed bands.

Entry into force

This specification shall enter into force on 17/02/2019 G

Frequency of operation

Following table is showing information on frequency bands, maximum output power and applicable specification:

Frequency band	Maximum Output Power or Magnetic Field	Spectrum access and mitigation requirements (Note 1)	ETSI Standard (Note 2)
863.000 - 870.000 MHz	25 mW e.r.p.	≤ 0.1 % duty cycle.	EN 300 220
865.000 – 868.000 MHz (Note 3)	500 mW e.r.p. Adaptive Power Control (APC) required.	≤ 10 % duty cycle for network access points. ≤ 2.5% duty cycle otherwise.	EN 303 204
868.000 - 868.600 MHz (Note 3)	25 mW e.r.p.	≤ 1 % duty cycle.	EN 300 220
868.700 - 869.200 MHz (Note 3)	25 mW e.r.p.	≤ 0.1 % duty cycle.	EN 300 220
869.400 - 869.650 MHz	500 mW e.r.p.	≤ 10% duty cycle	EN 300 220
869.700 - 870.000 MHz	5 mW e.r.p.	No requirement	EN 300 220
869.700 - 870.000 MHz	25 mW e.r.p.	≤ 1 % duty cycle.	EN 300 220
870.000 – 875.800 MHz	25 mW e.r.p.	≤ 1 % duty cycle.	EN 300 220
870.000 – 874.400 MHz	500 mW e.r.p. Adaptive Power Control (APC) required.	≤ 10% duty cycle for network access points. ≤ 2.5% duty cycle otherwise	EN 303 204
915.000 – 921.000 MHz	25 mW e.r.p.	≤ 0.1 % duty cycle.	EN 300 220
915.200 – 920.800 MHz	25 mW e.r.p.	≤ 1 % duty cycle.	EN 300 220
917.300 – 918.900 MHz	500 mW e.r.p. Adaptive Power Control (APC) required.	≤ 10% duty cycle for network access points. ≤ 2.5% duty cycle otherwise	EN 300 220

Note 1: in addition to minimum interference mitigation requirements listed in this column, the License - exempt LPWAN devices shall employ additional mitigation techniques prescribed in technology-specific standards including industry/manufacturer specifications. Such techniques include Adaptive Power Control, Adaptive Data Rate, Listen Before Transmit/Adaptive Frequency Agility, etc.

Note 2: in addition to standards listed in this column, the License - exempt LPWAN devices shall comply as relevant with existing and future technology-specific standards and specifications, including industry/manufacturer standards and ETSI System Reference Documents (i.e. TR 103 435, TR 103 526, etc.)

Note 3: use of the band 866-869 MHz by License - exempt LPWAN devices in KSA is currently allowed subject to band sharing with legacy TETRA Downlink operations. License - exempt LPWAN devices may therefore not claim protection from interference possibly caused by TETRA base station emissions.

Proof of compliance

It is required that test reports are obtained from a laboratory that has been accredited by a body that is a member of the ILAC Mutual Recognition Arrangement.

Technical requirements

Testing should be carried out to ensure compliance with the following specifications as applicable:

EN 300 220-2

Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD); Radio equipment to be used in the 25 MHz to 1000 MHz frequency range with power levels ranging up to 500 mW; Part 2: Harmonized EN covering essential requirements under article 3.2 of the R&TTE directive.

EN 303 204-2

Electromagnetic compatibility and Radio spectrum Matters (ERM); Network Based Short Range Devices (SRD); Radio equipment to be used in the 870 MHz to 876 MHz frequency range with power levels ranging up to 500 mW; Part 2: Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive

EN 301 489-1

Electromagnetic compatibility and Radio spectrum Matters (ERM); Electromagnetic Compatibility (EMC) standard for radio equipment and services; Part 1: Common technical requirements.

EN 301 489-3

Electromagnetic compatibility and Radio spectrum Matters (ERM); Electromagnetic Compatibility (EMC) standard for radio equipment and services; Part 3: Specific conditions for Short Range Devices (SRD) operating on frequencies between 9 kHz and 40 GHz.

If no issue or revision number is quoted along with the title of a technical specification, the latest published version should be used.

General

In addition to meeting the above requirements, all equipment must comply with the requirement of CIRC specifications GEN001, be safe and must not adversely affect other electrical equipment.

Additional requirements

A licence from CITC must be obtained for the network access points and base stations equipment before they can be used.

Obtaining technical standards

ETSI technical standards may be obtained free of charge for individual use from the ETSI website www.etsi.org.

Network information (only for network interfaces)

Further information on the characteristics and presentation of network interfaces can be found by visiting operator's website.

Document history

Description	Status	Data
	Issue 1	17/02/2019 G